



Opto-Link
Corporation Ltd

Polarization Maintaining ASE 1050nm Light Source

(Wavelength: 1022 ~ 1078nm)

The Polarization Maintaining (PM) 1050nm Amplified Spontaneous Emission (ASE) light source has broad wavelength range covering from 1022nm ~ 1078nm. This light source using Ytterbium-doped fiber produces excellent stability and output power.



Types

- Bench Top

Applications

- Fiber Optic Sensing
- Optical Tomography
- Component Characterization
- High Power Fiber Laser

Features

- High Output Power
- Good Spectral Stability
- PM Fiber Output



Opto-Link
Corporation Ltd

SPECIFICATIONS

ASE 1050nm Light Sources (with PM Fiber)

Parameter	Specifications	Units
Output Power	10	dBm
Operating Wavelength	1022 to 1078	nm
Spectral Density	> -16	dBm/nm
Output Stability (Over 8 hrs)	+/- 0.02	dB
Polarization Extinction Ratio	> 18	dB
Operating Temperature	0 to 40	°C
Storage Temperature	-10 to 70	°C
Fiber Type	PM Fiber	--
Power Supply	80 to 240, 43 to 63Hz	V AC
Display	Pump Laser Driving Current	--
Protection	Pump Laser Overheat	--
Interface	RS232	--
Connector Type	FC/APC, Aligned to Slow Axis	--
Dimensions	300 x 250 x 100	mm

ORDERING CODES

OLS15105 - B - P - -

Power	Code
+10 dBm	10
Others	XX

Connector Type	Code
FC/APC	FA
Others	XX

■ Opto-Link Corporation Ltd. reserves the right to make changes to the products described herein without notice.

COPYRIGHT © 2002-2007 Opto-Link Corporation Ltd.

Tel: +852 2480-6106 Fax: +852 2480-1621 Email: contact@optolinkcorp.com Website: www.optolinkcorp.com