



Opto-Link
Corporation Ltd

Optical Switch Benchtop

Optical Switches are designed following the standard of Telcordia GR-1029-CORE and GR-1221-CORE. They are compact-sized mechanical switches with excellent reliability. They are widely used in network switching, optical add/drop multiplexer (OADM), optical fiber ring protection and optical cross and connection (OXC) system. The switches are available with both the latching and non-latching configuration.

Applications

- Optical Add/Drop
- Fiber Optic Ring Protection
- Optical Cross Connection

Features

- Low Insertion Loss
- Excellent Stability
- On/Off, Add/Drop or Full Configuration



SPECIFICATIONS

4x4 Optical Switch

Parameter		Units
Operating Wavelength	1310/1550	nm
Switch Type	4 x 4	--
Insertion Loss	< 3.0	dB
Insertion Loss Stability	+/- 0.05	dB
Crosstalk	< -50	dB
Repeatability	+/- 0.05	dB
Life Time	10,000,000	cycles
Switching Time (Sequential Switching)	60	ms
Optical Handling Power	300	mW
Operating Temperature	0 to +50	°C
Storage Temperature	-20 to +60	°C
Voltage Supply	220	V AC
Interface	RS232	--
Fiber Type	SMF-28	--
Dimensions	Benchtop or 19" 1U Rackmount	--

*Above specifications are for device without connectors.

ORDERING CODES

