



Opto-Link
Corporation Ltd

PM Wavelength Division Multiplexer

Polarization Maintaining Wavelength Division Multiplexer (PMWDM) using Thin Film Filters technology (TFF) combine light with different wavelengths into a fiber or separate an optical signal into two fibers with special feature - maintaining polarization. This device provides low insertion loss and high return loss with high polarization extinction ratio.



Types

- Fused WDM
- Thin Film Filter WDM
- MultiMode WDM
- Polarization Maintaining WDM

Applications

- High Speed DWDM Systems
- Erbium-Doped Fiber Amplifiers
- CATV

Features

- Low Insertion Loss
- High Return Loss
- High Polarization Extinction Ratio
- Environmentally Stable




Opto-Link
Corporation Ltd

SPECIFICATIONS

Polarization Maintaining WDM (920/1064nm)

Parameter	Values	Units	
Passband	Wavelength Range	920 +/-5	nm
	Max. Insertion Loss	1.6	dB
	Min. Isolation @ Reflection Band Wavelength	25	dB
Reflection Band	Wavelength Range	1064 +/-20	nm
	Max. Insertion Loss	1.0	dB
	Min. Isolation @ Passband Wavelength	12	dB
Min. Extinction Ratio		20	dB
Min. Return Loss		50	dB
Max. Tensile Load		5	N
Max. Handling Power (CW)		500	mW
Fiber Length		1	m
Operating Temperature		-5 to +70	°C
Storage Temperature		-40 to +85	°C

*Above specifications are for device without connectors.



ORDERING CODES

OLWDM - P - [] - [] - []

Wavelength	Code
920Pass/1064Reflection	9210

Fiber Type	Code
250um bare fiber	25
900um loose tube	90
Others	XX

Connector Type	Code
No Connector	NC
FC/UPC	FU
SC/UPC	SU
FC/APC	FA
SC/APC	SA
Others	XX

Opto-Link Corporation Ltd. reserves the right to make changes to the products described herein without notice.

COPYRIGHT © 2002-2006 Opto-Link Corporation Ltd.

Tel: +852 2480-6106 Fax: +852 2480-1621 Email: contact@optolinkcorp.com Website: www.optolinkcorp.com